

- Allows user to partial pressure blend nitrox or any single gas for diving
- Allows for transfilling and boosting air to 3500 psi
- Portable in watertight Pelican Case iM2875

SPECIFICATIONS

MSB9000 | SKU NUVB-KIT-9000-1G

Drive	4" (10 cm)
Ratio	25:1
Weight	70 lb (32 kg)
Max Rated Inlet Pressure	4500 psi (310 bar)
Max Rated Outlet Pressure	4500 psi (310 bar)
Volume per Cycle	1.232 cu in (20.2 mL)
Max Air Drive Pressure	150 psi (11 bar)
Max Developed Output Pressure	3750 psi (259 bar)
Min Gas Supply Pressure	100 psi (7 bar)



SPECIFICATIONS

AG-30X | SKU NUVB-KIT-AG30X-1G

Drive	5.75" (14.6 cm)
Ratio	30:1
Weight	80 lb (36 kg)
Max Rated Inlet Pressure	4500 psi (310 bar)
Max Rated Outlet Pressure	4500 psi (310 bar)
Volume per Cycle	3.1 cu in (50.8 mL)
Max Air Drive Pressure	4500 psi (310 bar)
Max Developed Output Pressure	4500 psi (310 bar)
Min Gas Supply Pressure	100 psi (7 bar)

SPECIFICATIONS

AGT-15/30 | SKU NUVB-KIT-AGT15/30-1G

Drive	5.75" (14.6 cm)
Ratio	15:1
Weight	90 lb (41 kg)
Max Rated Inlet Pressure	5000 psi (345 bar)
Max Rated Outlet Pressure	5000 psi (345 bar)
Volume per Cycle	6.2 cu in (101.6 mL)
Max Air Drive Pressure	9000 psi (621 bar)
Max Developed Output Pressure	5000 psi (345 bar)
Min Gas Supply Pressure	50 psi (3.5 bar)

FEATURES

- Haskel MSB9000, AG-30 or AGT-15/30 booster installed
- Inlet for a single gas with quick disconnect
- Oil free pressure gauges
- Large 4" digital final pressure gauge
- Quick disconnect for final output fill whip
- Standard quick disconnect for first stage connection to drive from scuba cylinder
- Speed control needle valve for booster
- All components are oxygen cleaned to Nuvair Oxygen Clean Standards unless special ordered.